



When domestic water meters need to be installed underground, 'Meterfit' Meter Box Chambers provide the perfect solution. Fully assembled and pressure tested, they remove the need for on-site adjustment of internal joints.

The meter box (1) is installed first, at the bottom of the hole. Housing a non-return valve and meter carrier in Gunmetal or ABS, it provides a secure connection to the mains supply.

The guard pipe (2) simply clicks into the meter box. Standard guard pipes are 600mm high whilst other sizes are available.

A plastic top hat can then be added to the guard pipe along with

a iron boundary box.

METRON MARK III METER BOX CHAMBER

Code: MKC005



Product Description

Combined meter box and guard pipe with stopcock and meter carrier incorporated into a Gunmetal fitting.

Uses

The Gunmetal fitting makes the Mark III ideal for use in most applications including contaminated ground.

Technical Specification

- Grip-fit polypropylene meter box for simple guard pipe removal
- Dust/kemetal cap
- 3/4" female inlet and outlet
- Accepts most pipe materials when used with adaptors
- 3/4" rise and fall stopcock supplied with crutch head or 1/2" square head
- 200mm dia. PVC guard pipe
- 

METRON MARK VII METER BOX CHAMBER

Code: MKC002

Product Description

Combined meter box and guard pipe with isolating valve and meter carrier incorporated into an ABS fitting. Fitting available separately for wall-mounting.

Uses

The cost-effective MKC002 can be used where no ground contamination has taken place.

Technical Specification

- Grip-fit polypropylene meter box for simple guard pipe removal
- Dust/kemetal cap
- 25mm push-fit for MDPE pipes or 3/4" female iron can be adapted for copper and lead pipes
- 1/4 turn isolating valve
- 200mm dia. PVC guard pipe



METRON MARK VIII METER BOX CHAMBER

Code: MKC008

Product Description

Combined meter box and guard pipe with meter carrier, isolating valve, spindle and locking bush incorporated into a Gunmetal fitting.

Uses

The Gunmetal fitting makes the Mark VIII ideal for use in most applications including contaminated ground.

Technical Specification

- Grip-fit polypropylene meter box for simple guard pipe removal
- Dust/kemetal cap
- 3/4" female inlet and outlet
- Accepts most pipe materials when used with adaptors
- 1/4 turn isolating valve
- 200mm dia. PVC guard pipe

